

## Characteristics

Tailor-made length  
3-phase  
Decentralised system  
High pressure Airstop  
Preferred height: ask advice  
Aluzinc

## Models

ASE355F  
ASE400F\*  
ASE600/4.0  
ASE600/5.5  
ASE600/7.5

## Application

Outside doors  
Design  
Logistics

## Options

RAL colour  
Stainless steel  
Heating (electrical or water)  
Horizontal setup  
Single standing setup  
Double standing setup  
\* Heat pump

## Steering

5-step/Frequency converter (FRXM)




Masterveil Europe\*

Brusselbaan 192, BE-9320 Erembodegem

Tel: +32 (0)53 60 78 90 | Fax: +32 (0)53 60 78 99 | Mail: [office@deweerd.be](mailto:office@deweerd.be)

\* Masterveil is a subsidiary of Deweerdt BVBA

## Components and options horizontal and double standing setup



## Characteristics horizontal setup

- + strong solution which enables mounting at different heights
- be aware that an airflow sometimes effects people working nearby

## Characteristics double standing setup

- + very strong solution in protection against wind and pressure
- + horizontal airflow is well accepted by customers en employees
- be aware of limitation in door width


Masterveil Europe\*

Brusselbaan 192, BE-9320 Erembodegem

Tel: +32 (0)53 60 78 90 | Fax: +32 (0)53 60 78 99 | Mail: office@deweerdtdt.be

\* Masterveil is a subsidiary of Deweerdt BVBA

## Different shapes of outblow



## Optional: extended nozzle for in-built systems




Masterveil Europe\*

Brusselbaan 192, BE-9320 Erembodegem

Tel: +32 (0)53 60 78 90 | Fax: +32 (0)53 60 78 99 | Mail: [office@deweerdtd.be](mailto:office@deweerdtd.be)

\* Masterveil is a subsidiary of Deweerdt BVBA

## Airlock; one step further in protection



## Additional components

### Heaters:

- . Water heater\* – we are more than happy to do simulations for you
  - . Electrical heater – different types, mounted on pressure side
  - . Heater prepared for heat pump (not the regulation)
- When using a PGF water heater always use a filter box. The PGF model is made of galvanized steel and is connected to ducting by means of the PG module.

### Remark:

Use a differential pressure gauge to check the status of the bag filter. Pressure drop clean filter approx. 50 Pa, pressure drop polluted bag filter approx. 150 Pa

### Intake box with multiple connection possibilities:

- . Side, back, top or double side

## Masterveil Europe\*

Brusselbaan 192, BE-9320 Erembodegem

Tel: +32 (0)53 60 78 90 | Fax: +32 (0)53 60 78 99 | Mail: [office@deweerdtd.be](mailto:office@deweerdtd.be)

\* Masterveil is a subsidiary of Deweerdt BVBA